

STRYKER SLAT TREADMILL

TRUE heritage and engineering come together to provide your facility with the TRUE Stryker Slat Treadmill. The Stryker features a running surface of vulcanized rubber slats that are more durable and require less maintenance than the conventional conveyor belt system of traditional treadmills. The individual shock-absorbing slats provide a running surface closer to the natural feel of outdoor running for those looking for a more realistic training experience.

FEATURES

- Less downtime and overall lower cost-of-ownership than traditional treadmill
- Requires less maintenance; no need for tracking adjustments, waxing, or flipping of deck with slat system
- Ergonomic pistol-grip handles with thumb controls and center pod with quick speed and incline keys
- Over-molded rubber slat belt with 62 individual slats and running surface of 22"/55 cm x 60"/152 cm
- Three emergency stops for safety (on console, center pod, and safety key)



SPECIFICATIONS

DIMENSIONS (L X W X H)

72" L x 35" W x 64" H / 182 cm x 89 cm x 163 cm

SPEED

1 to 12.0 MPH / 1.6 to 19.3 KPH (0.5 increments)

INCLINE/DECLINE LEVELS

0% to 25% (-3% to 22% with Decline Kit)

PRODUCT WEIGHT

599 lbs / 271.7 kg

COLOR

Charcoal/Black

CONSOLE OPTIONS



ENVISION II
22" Touchscreen



ENVISION II
16" Touchscreen



ENVISION II
9" Touchscreen



SHOWRUNNER II
16" Integrated LCD



EMERGE II
LED Console



IGNITE II
LED Console



STRYKER SLAT TREADMILL

TECHNICAL SPECIFICATIONS

Power Source	120V/16A Dedicated (NEMA 5-20 Receptacle) 220-240V/8A Option Available														
Cord Length	12' / 3.7 M														
Power Factor Correction (PFC)	Standard														
Incline Motor	1,200 lbs. of thrust														
Speed Sensor	Optical														
Slat	62 vulcanized rubber slats - durometer of 75 shore														
End Rollers	58 mm diameter with shielded bearings														
Slatbelt Support Beraings	22 mm diameter with sealed bearings														
Frame Construction	Robotically Welded Heavy-Gauge Steel														
Speed Range	1 to 12.0 MPH / 1.6 to 19.3 KPH														
Incline/Decline Range	0% to 25% (-3% to 22% with Decline)														
Quick Access Control	Mechanical thumb switches and center pod with quick keys (speed and incline) as well as emergency stop														
Handrail Design	Extended Handrails with Molded Rubber, Moisture-Resistant Grips														
Contact Heart Rate Monitoring	Yes														
Wireless Heart Rate Monitoring	Polar® Compatible														
AVAILABLE CONSOLES	Envision II 22", Envision II 16", Envision II 9", ShowRunner II, Emerge II, Ignite II														
ASSET TRACKING	EcoFit Compatible														
SAFETY	<table border="0"> <tr> <td>Safety Clip</td> <td>Standard/Removable</td> </tr> <tr> <td>Extended Handrails</td> <td>Standard</td> </tr> <tr> <td>Large Straddle Covers</td> <td>Standard</td> </tr> <tr> <td>User Detection</td> <td>User Present Detection™</td> </tr> </table>	Safety Clip	Standard/Removable	Extended Handrails	Standard	Large Straddle Covers	Standard	User Detection	User Present Detection™						
Safety Clip	Standard/Removable														
Extended Handrails	Standard														
Large Straddle Covers	Standard														
User Detection	User Present Detection™														
REGULATORY APPROVALS	ETL UL1647, CSA, CE, EN957, (ISO 20957), FCC														
EXTRAS	Special Features Reading Rack, Two (2) 5" / 12.7 cm square water bottle holders, Accessory Tray (5" / 12.7 cm x 9" / 22.86 cm Textured Plastic)														
PHYSICAL SPECIFICATIONS	<table border="0"> <tr> <td>Footprint</td> <td>72" L x 35" W x 64" H / 182 cm x 89 cm x 163 cm</td> </tr> <tr> <td>Running Surface</td> <td>22"/55 cm x 60"/152 cm</td> </tr> <tr> <td>Machine Weight</td> <td>599 lbs / 271.7 kg</td> </tr> <tr> <td>Shipping Weight</td> <td>649 lbs / 294.3 kg</td> </tr> <tr> <td>Maximum User Weight</td> <td>500 lbs / 226.7 kg</td> </tr> <tr> <td>Deck Step-Up Height</td> <td>13" / 33.02 cm</td> </tr> <tr> <td>Portability</td> <td>Rear Retractable</td> </tr> </table>	Footprint	72" L x 35" W x 64" H / 182 cm x 89 cm x 163 cm	Running Surface	22"/55 cm x 60"/152 cm	Machine Weight	599 lbs / 271.7 kg	Shipping Weight	649 lbs / 294.3 kg	Maximum User Weight	500 lbs / 226.7 kg	Deck Step-Up Height	13" / 33.02 cm	Portability	Rear Retractable
Footprint	72" L x 35" W x 64" H / 182 cm x 89 cm x 163 cm														
Running Surface	22"/55 cm x 60"/152 cm														
Machine Weight	599 lbs / 271.7 kg														
Shipping Weight	649 lbs / 294.3 kg														
Maximum User Weight	500 lbs / 226.7 kg														
Deck Step-Up Height	13" / 33.02 cm														
Portability	Rear Retractable														
WARRANTY	<table border="0"> <tr> <td>Warranty Type</td> <td>Commercial (all dues paying facilities, regardless of usage)</td> </tr> <tr> <td>Frame</td> <td>7 Years</td> </tr> <tr> <td>Motor</td> <td>5 Years</td> </tr> <tr> <td>Parts</td> <td>3 Years</td> </tr> <tr> <td>Labor</td> <td>3 Years</td> </tr> <tr> <td>Console</td> <td>3 Years</td> </tr> </table>	Warranty Type	Commercial (all dues paying facilities, regardless of usage)	Frame	7 Years	Motor	5 Years	Parts	3 Years	Labor	3 Years	Console	3 Years		
Warranty Type	Commercial (all dues paying facilities, regardless of usage)														
Frame	7 Years														
Motor	5 Years														
Parts	3 Years														
Labor	3 Years														
Console	3 Years														

Warranties outside the U.S. and Canada may vary - Please contact your dealer for details. Specifications subject to change without notice.



btbfitness.ca | 403.265.1377

©2021 TRUE Fitness Technology, Inc

